

ELECTRONICS



DAC P1

Connect your active speaker or power amplifier to your digital audio ecosystem using these exceptional DACs. Both have multiple analogue and digital inputs, and volume and input selection on IR remote. Additionally the little P2 is also USB powered. An internal DSP IC handles the input selection and volume control of all inputs in the digital domain, resulting in very low distortion, noise and crosstalk. A very high-grade DAC IC converts the digital signal back into analog, resulting in high-grade audio reproduction.



DAC P2

	DAC P1	DAC P2
INPUTS	3 analog & 3 digital inputs (coaxial, optical, USB)	1 x stereo RCA, 1 x optical, 1 x USB
S/N RATIO (A-WEIGHTED)	95 dB analog, 115 dB digital	95 dB analog, 112 dB digital
REMOTE CONTROL	Input selection, standby power, volume, mute	Input selection, standby power, volume, mute
USB POWER	No	Yes
DIM. (HxWxD) mm	45 x 310 x 160	45 x 122 x 122
NET WEIGHT	1.9 kg	0.7 kg

SBP 101

This tiny gadget has large sound value. It allows you to stream, via bluetooth, from your phone / tablet / PC to active speakers or amplifiers. The SBPs super-low latency and noise, and detailing will leave you astounded.

DE 4348

The DE 4348 is a high performance multi-channel processor that forms unique packages with Sonodyne active speakers. It is also very useful in custom installation for mini cinemas and corporate boardrooms

- HDMI/4K (2160 x 3840)
- On screen display (OSD)
- High performance preamplifier with 7.2 unbalanced and balanced output
- Low magnetic flux leakage massive toroidal transformer
- 32 bit (TI, CO.) DSP decoding: Dolby TrueHD/ Dolby Digital Plus/ Dolby Digital/ DTS-HD Master Audio/ DTS ES



DSA 320

We are proud to announce our newest integrated amplifier, the DSA 320. At a slim 1.7", it employs a large toroidal transformer and intelligent heat sinking to deliver, noiselessly, oodles of power with excellent headroom. Both analogue and digital inputs (optical, coaxial, USB) are present with i/p selection and level control on remote. A minimalistic design with aluminum extrusion edges gives it an elegant look worthy of your mantlepiece.

POWER	125 W x 2 @ 4 Ohm; 85 W x 2 @ 8 Ohm
THD @ RATED POWER	< 0.1 %
INPUTS	2 x stereo RCA, 1 x coaxial, 1 x optical SPDIF, 1 x USB
OUTPUTS	Pre out: XLR, Pre out: RCA, Phones: TRS
S/N RATIO, A-WEIGHTED	Analogue 90 dB; Digital 100 dB
DIMENSIONS (HxWxD)mm	45 x 445 x 380
NET WEIGHT	9.2 kg