



A-LIGN 400S

column speakers

- Monopole line array including 16 drivers
- Wide horizontal coverage
- 2 way design
- Aluminium cabinet
- Wall mount provision
- Black/ white colour

DESCRIPTION	2 way monopole line array
ENCLOSURE	5mm extruded aluminium with PU paint
GRILL	Perforated nylon
TRANSDUCER COMPLEMENTS	8 x 3" pp cone woofer, 8 x dome tweeter with wave guide
INPUT	Twist lock
PARALLEL LINK	Euroblock
SENSITIVITY (1W/1M) half space	94dB
MAXIMUM SPL	121dB
NOMINAL IMPEDANCE	4Ω
CROSSOVER FREQUENCY	1.8kHz
FREQUENCY RESPONSE (-3dB)	180Hz ~ 20kHz
FREQUENCY RANGE (-10dB)	140Hz ~ 25kHz
COVERAGE PATTERN	110° H x 20° V
CONTINUOUS POWER HANDLING	200W
RECOMMENDED AMP POWER	300W
DIMENSIONS (HxWxD)mm	1194 x 125 x 110
NET WEIGHT	9.8kg
MOUNTING OPTIONS	A400 PM, A400 WB

Due to continuous improvements, all specifications are subject to change

Products of the **MUKHERJEE INNOVATION CENTRE**

SONODYNE, 98 NB Block E New Alipore, Kolkata 700053, INDIA 1-800-123-37-36 • response@sonodyne.com • www.sonodyne.com