



Shown here with the Roarr 1108 powered subwoofer

The Micro 3001 and 3002 are new satellite speakers. But don't let their small size fool you. These are serious speakers and they employ custom transducers and elaborate crossovers to provide a detailed sound that is loud and clear. The enclosure is ABS (moulded plastic) that gives the Micro a unique shape which blends into your living space. The products are sold separately or as a Micro HTS package with the rugged Roarr 1108. You may install the Micros using the keyhole slot or with universal brackets (included). So if you are looking for high quality music or cinema sound experience in your premium space, choose the new Micro from Sonodyne.

	MICRO 3001	MICRO 3002
DESCRIPTION	2 way speaker , ported	2 way speaker , ported
ENCLOSURE	ABS	ABS
TRANSDUCER COMPLEMENTS: HF	0.5 inch polycone tweeter	0.5 inch polycone tweeter
TRANSDUCER COMPLEMENTS: LF	3 inch woofer	2 x 3 inch woofer
RECOMMENDED AMPLIFIER POWER	40 - 100 watt	40 - 120 watt
NOMINAL IMPEDANCE	8 Ohm	8 Ohm
SENSITIVITY (1 W 1M)	87 dB	90 dB
FREQUENCY RESPONSE (-3 dB)	100Hz - 20kHz	100Hz - 20kHz
FREQUENCY RANGE (-10 dB)	80Hz - 22kHz	70Hz - 22kHz
CROSSOVER FREQUENCY	6.5 kHz	3.5 kHz
INPUTS	Binding post	Binding post
COLOURS	Black / White	Black / White
DIMENSIONS (HXWXD)	171 mm x 100 mm x 108 mm	100 mm x 261 mm x 100 mm
NET WEIGHT	0.75 kg	1.3 kg
MOUNTING OPTIONS	Wall mount bracket (included)	Wall mount bracket (included)
PACKED IN	Pairs	Single

For detailed specifications visit www.sonodyne.com | Due to continuous improvements, all specifications are subject to change