

SONODYNE®

SVM SERIES

speech microphones

- UHF wireless microphone with dual channels
- 2 versions: DH1: dual handheld or LH1 (1 handheld, 1 lapel)
- Frequency 865~867MHz
- Plastic handheld microphone with high quality capsule
- Power supply: 12V/1A
- Contents include 1 connecting cable and 4 x 1.5VAA batteries



RECEIVER

CARRIER WAVE FREQ. RANGE	865 ~ 867MHz
CARRIER WAVE STABILITY	10ppm
SENSITIVITY	-105dB @ sinad=12dB
SIGNAL TO NOISE RATIO	> 105dB
T.H.D.	<0.5% @ 1kHz
IMAGE REJECTION	85dB typical
SPURIOUS REJECTION	75dB typical
FREQUENCY RESPONSE	40Hz ~ 18kHz
WORKING DISTANCE	> 200 ft
AF OUTPUT IMPEDANCE	2.2kΩ

MAX OUTPUT LEVEL

Balanced :0~400mV,
Unbalanced : 0~200mV

DISPLAY

LCD

POWER SUPPLY

External DC Power supply, 1A, 12V DC

OUTPUT CONNECTOR

XLR balanced socket,
unbalanced TRS 6.35mm socket

TRANSMITTER

TRANSMITTER POWER

30mW

SPURIOUS EMISSION

<40dB with carrier

DISPLAY

LCD

BATTERY

1.5V x 2 pcs

BATTERY LIFE

6-8 hours

Due to continuous improvements, all specifications are subject to change