

SONODYNE®

MADE IN INDIA
since 1970

SPA SERIES

portable loudspeakers

- Active and Passive versions
- High efficiency wide band D Class amplifiers, bi-amplified
- Custom transducers
- Rugged portable cabinets
- Wall mount
- Floor monitor
- Pole mount
- 2 inputs: mic and line
- 2 band EQ



	SPA 108	SPA 110	SPA 112	SPA 115
TRANSDUCERS	LF: 8" with 1.5" VC, HF: 1" HLCD with 1.1" VC	LF: 10" with 2" VC, HF: 1" HLCD with 1.1" VC	LF: 12" with 2.5" VC, HF: 1" HLCD with 1.1" VC	LF: 15" with 3" VC, HF: 1" HLCD with 1.75" VC
FREQ. RESPONSE (-3dB)	75Hz ~ 17kHz	65Hz ~ 17kHz	65Hz ~ 17 kHz	60Hz ~ 17kHz
POWER HANDLING PROGRAM	200W	300W	500W	600W
CABINET	Plastic	Plastic	Plastic	Plastic
MOUNTING	Wall bracket, pole mount, floor monitor	Wall bracket, pole mount, floor monitor	Pole mount, floor monitor	Pole mount, floor monitor
DIMENSIONS (H x W x D) mm	400 x 260 x 227	510 x 330 x 220	580 x 390 x 320	685 x 470 x 385
NET WEIGHT	7.6kg	10.7kg	15.6kg	20.0kg

	SPA 108P	SPA 110P	SPA 112P	SPA 115P
TRANSDUCERS	LF: 8" with 1.5" VC, HF: 1" HLCD with 1.1" VC	LF: 10" with 2" VC, HF: 1" HLCD with 1.1" VC	LF: 12" with 2.5" VC, HF: 1" HLCD with 1.1" VC	LF: 15" with 3" VC, HF: 1" HLCD with 1.75" VC
FREQUENCY RESPONSE (-3dB)	70Hz - 17kHz	60Hz ~ 17kHz	60Hz ~ 17kHz	55Hz ~ 17kHz
AMPLIFIER POWER PROGRAM	200W	300W	500W	700W
INPUTS	Balanced mic: 1; Balanced line: 1; Balanced Mix Out: 1		Balanced mic: 1; Balanced line: 1; Balanced Mix Out: 1	
USB SD CARD	Support WMA, WAV, mp3 files; Controls: Play / Pause, Stop, Repeat, Next , Previous			
BT	Version 4.2	Version 4.2	Version 4.2	Version 4.2
MOUNTING	Wall bracket, pole mount, floor monitor		Pole mount, floor monitor	
DIMENSIONS (H x W x D) mm	400 x 260 x 227	510 x 330 x 220	580 x 390 x 320	685 x 470 x 385
NET WEIGHT	9.3kg	12.0kg	16.9kg	21.3kg

Due to continuous improvements, all specifications are subject to change